

EPS-350C CS (5.33:1)							
PROPELLE	Volts	Amps	Spinta		Potenza (w)	efficienza	
	(V)	(A)	(g)	(oz)		(g/w)	(oz/w)
EP8060	8.04	7	320	11.20	58.80	5.44	0.19
EP8060	9.06	8.06	380	13.30	82.56.00	0,2083333	0.16
EP8060	10.08	10.02	450	0,6770833	110.16.00	4.08	0.14
EP9047	7.02	6.06	318	11.13	47.52.00	0,2979167	0.23
EP9047	8.04	8.03	388	13.58	69.72	5.57	0.19
EP9047	9.06	10.03	470	16.45	98.88	0,21875	0.17
EP9050	7.02	5.02	280	0,4305556	37.44.00	7.48	0.26
EP9050	8.04	6.07	364	0,5513889	56.28.00	6.47	0.23
EP9050	9.06	8.05	450	0,6770833	81.60	5.51	0.19
EP9050	10.08	10.02	525	18.38	110.16.00	0,2201389	0.17
EP9070	7.02	8	329	11.52	57.60	0,2576389	0.20
EP9070	8.04	9.03	365	0,5541667	78.12.00	0,2131944	0.16
EP9070	9.06	11.02	420	0,6319444	107.52.00	0,1881944	0.14
EP1047	6	6.05	300	10.50	39.00.00	0,3395833	0.27
EP1047	7.02	8.08	410	14.35	63.36.00	6.47	0.23
EP1047	8.04	10.03	470	16.45	86.52.00	5.43	0.19
EP1047	9.06	12.08	540	0,8125	122.88	4.39	0.15
EP1060	6	5.03	267	9.35	31.80	8.40	0.29
EP1060	7.02	6.09	345	12.08	49.68	0,3152778	0.24
EP1060	8.04	8.08	439	15.37	73.92	0,2736111	0.21
EP1060	9.06	10.06	520	18.20	101.76	5.11	0.18